

Out-Pace Upper Control Arm Part Number Key

Only used if customizations are made.

32A8-090LO-150

32 - Bushing A-Frame
36 - Bearing A-Frame

A - Aluminum Shaft
S - Steel Shaft

0 - 6" Center Shaft
2 - 6 1/2" Center Shaft
8 - 6 7/8" Center Shaft
4 - 7 3/4" Center Shaft
S - Slotted Shaft
P - Pocket (Slugged) Shaft

077 - 7.75"
080 - 8.00"
082 - 8.25"
085 - 8.50"
087 - 8.75"
090 - 9.00"
092 - 9.25"
095 - 9.50"
097 - 9.75"
100 - 10.00"
102 - 10.25"
105 - 10.50"
107 - 10.75"
110 - 11.00"
112 - 11.25"
115 - 11.50"
117 - 11.75"

C - Centered BJ
O - BJ Offset 1.25"

L - Large Bolt-in Plate
M - Small Bolt-in Plate
S - Screw-in Collar
T - Tipped Collar 13°

DBW - Double BJ Plate Welded
DBL - Double BJ Plate Loose
O-xxx Custom Offset (decimal format without decimal)
ex. O-150 designates 1 1/2" Offset

If **custom offset** and **double BJ plates** are used on same part: State **offset** first then **double plate** (ex. O-150-DBW).